

MEDIDAS DE ESPÁRRAGOS PARA BRIDAS CLASE ANSI 150 A 2500

Dimensiones (pulgadas) ANSI/ASME 150 - 600 lb

Flange Size	150 lb (1/16" RF)				300 lb (1/16" RF)				400 lb (1/4" RF)				600 lb (19/4" RF)			
Nominal Pipe Size (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)
1/2	4	1/2	1-3/4	2-1/4	4	1/2	2	2-1/2	Para estos tamaños se utilizan bridas de 600 lb				4	1/2	2-1/2	3
3/4	4	1/2	2	2-1/2	4	5/8	2-1/2	3					4	5/8	2-3/4	3-1/2
1	4	1/2	2	2-1/2	4	5/8	2-1/2	3					4	5/8	3	3-1/2
1-1/4	4	1/2	2-1/4	2-3/4	4	5/8	2-3/4	3-1/4					4	5/8	3-1/4	3-3/4
1-1/2	4	1/2	2-1/4	2-3/4	4	3/4	3	3-1/2					4	3/4	3-1/2	4-1/4
2	4	5/8	2-3/4	3-1/4	8	5/8	3	3-1/2					8	5/8	3-1/2	4-1/4
2-1/2	4	5/8	3	3-1/2	8	3/4	3-1/4	4					8	3/4	4	4-3/4
3	4	5/8	3	3-1/2	8	3/4	3-1/2	4-1/4					8	3/4	4-1/4	5
3-1/2	8	5/8	3	3-1/2	8	3/4	3-3/4	4-1/4					8	7/8	4-3/4	5-1/2
4	8	5/8	3	3-1/2	8	3/4	3-3/4	4-1/2	8	7/8	4-3/4	5-1/4	8	7/8	5	5-3/4
5	8	3/4	3-1/4	3-3/4	8	3/4	4	4-3/4	8	7/8	5	5-1/2	8	1	5-3/4	6-1/2
6	8	3/4	3-1/4	4	12	3/4	4-1/4	4-3/4	12	7/8	5-1/4	5-3/4	12	1	6	6-3/4
8	8	3/4	3-1/2	4-1/4	12	7/8	4-3/4	5-1/2	12	1	6	6-1/2	12	1-1/8	7	7-1/2
10	12	7/8	3-3/4	4-1/2	16	1	5-1/4	6-1/4	16	1-1/8	6-3/4	7-1/4	16	1-1/4	7-3/4	8-1/2
12	12	7/8	4	4-3/4	16	1-1/8	5-3/4	6-3/4	16	1-1/4	7-1/4	7-3/4	20	1-1/4	8	8-3/4
14	12	1	4-1/4	5-1/4	20	1-1/8	6	7	20	1-1/4	7-1/2	8	20	1-3/8	8-1/2	9-1/4
16	16	1	4-1/2	5-1/4	20	1-1/4	6-1/2	7-1/2	20	1-3/8	8	8-1/2	20	1-1/2	9-1/4	10
18	16	1-1/8	4-3/4	5-3/4	24	1-1/4	6-3/4	7-3/4	24	1-3/8	8-1/4	8-3/4	20	1-5/8	10	10-3/4
20	20	1-1/8	5-1/4	6-1/4	24	1-1/4	7	8	24	1-1/2	9	9-1/2	24	1-5/8	10-3/4	11-1/4
24	20	1-1/8	5-3/4	6-3/4	24	1-1/2	7-3/4	9	24	1-3/4	10	10-1/2	24	1-7/8	12-1/4	13

Dimensiones (pulgadas) ANSI/ASME 900 - 2500 lb

Flange Size	900 lb (1/4" RF)				1500 lb (1/4" RF)				2500 lb (1/4" RF)			
Nominal Pipe Size (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)	Number of Bolts	Diameter of Bolts (in)	Length of Headed Bolts (in)	Length of Stud Bolts (in)
1/2	Para estos tamaños se utilizan bridas de 1500 lb				4	3/4	3-1/2	4-1/4	4	3/4	4-1/4	4-3/4
3/4					4	3/4	3-3/4	4-1/2	4	3/4	4-1/4	5
1					4	7/8	4-1/4	5	4	7/8	4-3/4	5-1/2
1-1/4					4	7/8	4-1/4	5	4	1	5-1/4	6
1-1/2					4	1	4-3/4	5-1/2	4	1-1/8	6	6-3/4
2					8	7/8	5	5-3/4	8	1	6-1/4	7
2-1/2					8	1	5-1/2	6-1/4	8	1-1/8	7	7-3/4
3	8	7/8	5	5-3/4	8	1-1/8	6-1/4	7	8	1-1/4	8	8-3/4
3-1/2	-	-	-	-	-	-	-	-	-	-	-	-
4	8	1-1/8	6	6-3/4	8	1-1/4	7	7-3/4	8	1-1/2	9-1/4	10
5	8	1-1/4	6-3/4	7-1/2	8	1-1/2	9	9-3/4	8	1-3/4	11	11-1/4
6	12	1-1/8	7	7-1/2	12	1-3/8	9-1/2	10-1/4	8	2	13	13-1/2
8	12	1-3/8	8	8-3/4	12	1-5/8	10-3/4	11-1/2	12	2	14-1/2	15
10	16	1-3/8	8-1/2	9-1/4	12	1-7/8	12-3/4	13-1/4	12	2-1/2	18-1/2	19-1/4
12	20	1-3/8	9-1/4	10	16	2	14-1/4	14-3/4	12	2-1/2	20-1/2	21-1/4
14	20	1-1/2	10	10-3/4	16	2-1/4	15-1/2	16				
16	20	1-5/8	10-1/2	11-1/4	16	2-1/2	17	17-1/2				
18	20	1-7/8	12-1/4	12-3/4	16	2-3/4	18-3/4	19-1/2				
20	20	2	13	13-3/4	16	3	20-1/2	21-1/4				
24	20	2-1/2	16-1/2	17-1/4	16	3-1/2	23-1/2	24-1/4				

Specifications to A193, B7, L7, B16 & B8M A194, 2H, G4 & G8M Stainless Steel SS316 and SS304 Grade 5 & Grade 8-8, A325 High Tensile & M.S.

Types: - Stud-Bolts, Hex Nut, HHMB.